

DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHION

My Account

Search: Quick/Number Boolean Advanced Derwent

Help

No active trail

Select PR

Stop Tracking

The Delphion Integrated View

☒ PDF | More choices...

Get Now:

View: INPADOC | Jump to: Top

Go to: Derwent

Tools: Add to Work File: Create new Work File Add

☒ Email this to a friend

Title: JP200035555A2: PRODUCTION OF DIELS-ALDER REACTIONAL PRODUCT USING PREHEATER

Derwent Title: Manufacture of diels-alder reaction product especially tetracyclo dodecene involves pre-heating cyclopentadiene derivative and alpha-olefin through pipe like pre-heater containing mixer
[Derwent Record]

Country: JP Japan
Kind: A2 Document Laid open to Public inspection
Inventor: AIDA FUYUKI;
SUZUKI TAKASHI;
MATSUMURA YASUO;
Assignee: NIPPON PETROCHEM CO LTD
News, Profiles, Stocks and More about this company


Published / Filed: 2000-12-26 / 1999-06-10

Application Number: JP1999000163761

IPC Code: C07C 2/50; C07C 13/42; C07C 13/66;

Priority Number: 1999-06-10 JP1999000163761

Abstract: PROBLEM TO BE SOLVED: To produce the subject product having a high effective yield of an α -olefin in a reaction by a stable operation over a long period by preheating a specific diene compound with the α -olefin, heating up the resultant mixture and then carrying out the reaction.
SOLUTION: A cyclopentadiene derivative (e.g. cyclopentadiene) and an α -olefin (e.g. ethylene) are passed through a heat exchanger as a preheater having a mixing element in a pipe conduit, preheated and then reacted to produce the above product



DELPHION AVAILABLE COPY

(e.g. tetracyclododecene). The preheating is preferably carried out by passing both through the interior of the preheater having the plurality of mixing elements so as to provide ≥ 100 Reynolds' number (Re) represented by the formula $Re=DG/\mu$ [D is the inside diameter (m); G is the mass velocity (kg/m²s); μ is the viscosity (kg/m.s)]. A fluid is preferably heated at $\geq 130^{\circ}\text{C}$ with the preheater. The reactional pressure is preferably ≤ 10 MPa and the space velocity is 0.001-100 h⁻¹.

COPYRIGHT: (C)2000,JPO

Family: None

CHEMABS 134(05)056440W CHEMABS 134(05)056440W

Other Abstract
Info:



Nominate this for the Gallery...

THOMSON
★

Copyright © 1997-2005 The Thomson Corporation
Subscriptions | Web Seminars | Privacy | Terms & Conditions | Site Map | Contact Us | Help